



- GLARE CONTROL
- NATURAL LIGHT
- LIGHTING CONTROL
- FLICKER MANAGEMENT



## Thrive Reflector

SKU	W	Lm @4000K/@90CRI/55°	Tilt (T) Rotation (R) °	Cutout (mm)	Dimensions (mm)
G2-TR12TA	12W	840	30°T 355°R	Ø 76	
G2-TR12T	12W	840	Fixed	Ø 76	
G2-TR12RA	12W	840	30°T 355°R	Ø 75	
G2-TR12R	12W	840	Fixed	Ø 75	
G2-TR12SA	12W	840	30°T	Ø 75	
G2-TR12RA2	12W	1020	30°T 355°R	Ø 95	
G2-TR12RA3	12W	1020	30°T 355°R	Ø 95	
G2-TR12RW	12W	600	Fixed	Ø 75	

### Physical

**Housing** Aluminium  
**Reflector Finish** Black, Specular Silver, Matte Silver  
**Trim Finish** White, Black  
**Mounting Type** Trimless, Recessed

### Electrical

**Voltage**  
 AC 220-240v 50/60Hz  
**Control**  
 Non-dimmable, Triac, 1-10V, DALI

### Optical

**Beam Angle**

15° 24° 38° 55° Wash

**CCT** 2700, 3000, 4000, 5000K

**CRI** 90, Thrive\*

**UGR** < 19

**Efficiency** 50-100lm/W

### Certification

**Warranty** 5 years

**Category**  
 AS/NZS 60598.2.2A  
 TM21 report on request



SKU	W	Lm @4000K/@90CRI/55°	Tilt (T) Rotation (R) °	Cutout (mm)	Dimensions
G2-TR24RA	24W	2198	30°T 355°R	Ø 100	
G2-TR24R	24W	2161	Fixed	Ø 100	
G2-TR24SA	24W	2156	25°T	Ø 100	
G2-TR-24RA2	24W	2472	30°T 355°R	Ø 110	
G2-TR-24RA3	24W	2332	30°T 355°R	Ø 110	
G2-TR-33RA	33W	2784	25°T 355°R	Ø 125	
G2-TR33R	33W	2848	Fixed	Ø 125	
G2-TR-33SA	33W	2795	25°T	Ø 125	
G2-TR-33RA2	24W	3292	30°T 355°R	Ø 130	
G2-TR-33RA3	33W	2996	30°T 355°R	Ø 130	



\* Thrive LED specifications