

K1



General data:

luminaire body:	aluminum
mounting type:	ground foundation
Ingress protection IP:	65
operating temperature range:	from -20°C to +45°C
lifetime L80B10:	100 000 h
impact protection IK:	10

Electrical data:

nominal voltage:	220-240V AC
Nominal frequency:	50-60Hz
luminaire nominal power:	13W, 25W
protection class:	I
Contains light source:	yes
dimming:	On-Off, DALI
wiring :	standard





Optical data:

optical system:	opal diffuser
material:	glass
Light emission:	direct
light distribution:	symmetrical

Lighting data:

light source:	LED
colour rendering index:	CRI>80
tolerance of luminous flux:	+/-10%
colour tolerance SDCM:	SDCM<3

Photometric body



C- colour

E- electronics

O- On-Off

D- Dali



white
03

grey
06

anthracite
70

black
05

Catalogue code	Luminaire light flux	Power	Effectiveness	Color temperature	CRI/RA	Weight	Dimensions
9304.83EC	336lm	13W	27lm/W	3000K	≥80	7,5kg	H=800mm
9304.84EC	350lm	13W	27lm/W	4000K	≥80	7,5kg	H=800mm
9305.83EC	631lm	25W	26lm/W	3000K	≥80	7,5kg	H=800mm
9305.84EC	658lm	25W	26lm/W	4000K	≥80	7,5kg	H=800mm

Accessories

ground foundation Type A

catalogue code: 90.15 + 90.15.02



ground foundation Type B

catalogue code: 90.16.02

