

OLLIE 60 POWER LED



General data:

luminaire body:	PMMA/inox
mounting type:	to the ground, on an adjustable handle
ingress protection IP:	65
operating temperature range:	from -40° to +45°
lifetime L80B10:	100 000h

Electrical data:


nominal voltage:	220-240V AC
nominal frequency:	50-60Hz
luminaire nominal power:	3W, 11W, 21W, 35W
protection class:	I
connection:	wire 3x0,75mm ² (5x0,75mm ² for DALI)
wiring :	through, standard
connection wire:	0,5m
dimming:	ON-OFF, DALI
power supply:	inside the luminaire

Optical data:

optical system:	lens
material:	PMMA
light emission:	direct
light distribution:	symmetrical

Lighting data:

light source:	LED
luminous flux from luminaire 3W, 11W, 21W, 35W:	264 lm, 1188 lm, 2376 lm, 3960 lm
luminous efficacy from luminaire 3W, 11W, 21W, 35W	88 lm/W, 108 lm/W, 113 lm/W, 113 lm/W
colour temperature:	2700K, 3000K, 4000K
colour rendering index:	CRI>80
colour tolerance SDCM:	SDCM<3
tolerance of luminous flux:	+/-10%



The Ollie wall luminaire is designed for illumination of facades with modern and classical architecture. Luminaire diffuser with a diameter of 60mm is made of PMMA. Thanks to the mounting brackets, it is possible to precisely position the luminaire in relation to the illuminated surface. Ollie family consists of luminaires with different power and dimensions while maintaining a uniform design.

Catalogue code	Luminaire light flux	Power	Color temperature	CRI/RA	Weight	Dimensions	Box dimensions
9103.02ELW	1117lm	11W	2700K	≥80	1,3kg	380x60x(123-147)mm	450x200x150mm
9103.03ELW	1117lm	11W	3000K	≥80	1,3kg	380x60x(123-147)mm	450x200x150mm
9103.04ELW	1188lm	11W	4000K	≥80	1,3kg	380x60x(123-147)mm	450x200x150mm

Accessories

connector IP68 3-pole

catalogue code 124.00

