


# UFO



## General data:

|                              |  |
|------------------------------|--|
| Luminaire body:              | aluminum                               |
| Mounting type:               | on an adjustable holder, to the ground |
| Ingress protection IP:       | 66                                     |
| Operating temperature range: | from -40° to +45°                      |
| Lifetime L80B10 :            | 100 000h                               |
| Impact protection IK:        | 07                                     |

## Electrical data:


|                          |                            |
|--------------------------|----------------------------|
| Nominal voltage:         | 220-240V AC                |
| Nominal frequency:       | 50-60Hz                    |
| Luminaire nominal power: | 2W, 3W                     |
| Protection class:        | I                          |
| Connection:              | wire 3x0,75mm <sup>2</sup> |
| Wiring:                  | through, standard          |
| Connection wire:         | 0,5m                       |
| Dimming:                 | ON- OFF                    |
| Power supply:            | inside the luminaire       |

## Optical data:

|                     |             |
|---------------------|-------------|
| Optical system:     | lens        |
| Material:           | PC          |
| Light emission:     | direct      |
| Light distribution: | symmetrical |

## Lighting data:

|  |                                     |
|--|-------------------------------------|
| Light source:                            | LED                                 |
| Luminous flux from luminaire 2W, 3W:     | 153 lm, 306 lm                      |
| Luminous efficacy from luminaire 2W, 3W: | 146 lm/W                            |
| Colour temperature:                      | 2700K, 3000K, 4000K (option: 6500K) |
| Colour rendering index:                  | CRI>80 (options: CRI>90)            |
| Colour tolerance SDCM:                   | SDCM<3                              |
| Tolerance of luminous flux:              | +/-10%                              |




UFO is an outdoor luminaire with specialized optics designed to illuminate window recesses and facade elements. The luminaire distribute the light around the recess, creating a beautiful effect, giving lighting and decoration at the same time. The high protection class IP66 gives the luminaire high resistance to bad weather conditions, moisture and dust. Thanks to the adjustable handle, it is possible to precisely adjust the direction of the light beam.

**L- beam angle**  
31-165°x3°

**W - wiring**  
T - through  
S - standard

**C - colour**

**E- electronics**  
O- On-Off



| Catalogue code | Luminaire light flux | Power | Color temperature | CRI/RA | Weight | Dimensions     | Box dimensions |
|----------------|----------------------|-------|-------------------|--------|--------|----------------|----------------|
| 9182.02ELCW    | 134lm                | 2W    | 2700K             | ≥80    | 0,7 kg | Ø 90mm, H=75mm | 200x200x200mm  |
| 9182.03ELCW    | 144lm                | 2W    | 3000K             | ≥80    | 0,7 kg | Ø 90mm, H=     | 200x200x200mm  |
| 9182.04ELCW    | 153lm                | 2W    | 4000K             | ...    | 0,7 kg | Ø 90mm, H=75mm | 200x200x200mm  |
| 9183.02ELCW    | 268lm                | 3W    | 2700K             | ≥80    | 0,7 kg | Ø 90mm, H=75mm | 200x200x200mm  |
| 9183.03ELCW    | 288lm                | 3W    | 3000K             | ≥80    | 0,7 kg | Ø 90mm, H=75mm | 200x200x200mm  |
| 9183.04ELCW    | 307lm                | 3W    | 4000K             | ≥80    | 0,7 kg | Ø 90mm, H=75mm | 200x200x200mm  |

## Accessories

connector IP68 3-pole

catalogue code 124.00



embranchment IP67

catalogue code 90.10

