


UFO LV



General data:

Luminaire body:	aluminum
Mounting type:	on an adjustable holder, to the ground
Ingress protection IP:	66
Ingress protection IP:	from -40° to +45°
Lifetime L80B10 :	100 000h
Impact protection IK:	07

Electrical data:


Nominal voltage:	700mA, max. 3V DC
Luminaire nominal power:	2W
Protection class:	III
Connection:	wire 2x1mm ²
Wiring:	standard
Connection wire:	0,5m
Ściemnianie/zasilacze str. 309:	ON-OFF, DALI, DMX, CASAMBI

Optical data:

Optical system:	lens
Material:	PC
Light emission:	direct
Light distribution:	symmetrical


Lighting data:

Light source:	LED
Luminous flux from luminaire:	306 lm
Luminous efficacy from luminaire:	146 lm/W
Colour temperature:	2700K, 3000K, 4000K (option: 6500K)
Colour rendering index:	CRI>80 (options: CRI>90)
Colour tolerance SDCM:	SDCM<3
Tolerance of luminous flux:	+/-10%



UFO is an outdoor luminaire with specialized optics designed to illuminate window recesses and facade elements. The luminaire distribute the light around the recess, creating a beautiful effect, giving lighting and decoration at the same time. The high protection class IP66 gives the luminaire high resistance to bad weather conditions, moisture and dust. Thanks to the adjustable handle, it is possible to precisely adjust the direction of the light beam.

L- beam angle
31-165°x3°



C - colour

Catalogue code	Light source	Luminaire light flux	Power	Color temperature	Weight	Dimensions	Box dimensions
9184.020LC	LED	268lm	2W	2700K	0,7 kg	Ø 90mm, h=75mm	200x200x200mm
9184.030LC	...	288lm	2W	3000K	0,7 kg	Ø 90mm, H=75mm	200x200x200mm
9184.040LC	...	307lm	2W	4000K	0,7 kg	Ø 90mm, H=75mm	200x200x200mm

Accessories

connector IP68 3-pole

catalogue code 124.00



embranchment IP67

catalogue code 90.10

