

UFO RGBW LV




General data:

Luminaire body:	aluminum
Mounting type:	on an adjustable holder, to the ground
Ingress protection IP:	66
Operating temperature range:	from -40° to +45°
Lifetime L80B10 :	100 000h
Odporność na uderzenia IK:	07



Electrical data:

Nominal voltage:	max. 4x350mA, max. 4x3V DC
power supply/driver:	to be ordered separately
Luminaire nominal power:	4W
Protection class:	III
Connection:	wire 8x0.3mm ²
Wiring:	standard
Connection wire:	0.5m
Dimming/power supply p. 310, 312:	ON-OFF, DALI, DMX, CASAMBI



Optical data:

Optical system:	lens
Material:	PC
Light emission:	direct
Light distribution:	symmetrical


Lighting data:

Light source:	LED
Luminous flux from luminaire RGBW:	200 lm
Tolerance of luminous flux:	+/-10%

UFO is an outdoor luminaire with specialized optics designed to illuminate window recesses and facade elements. The luminaire distributes the light around the recess, creating a beautiful effect, giving lighting and decoration at the same time. The high protection class IP66 gives the luminaire high resistance to bad weather conditions, moisture and dust. Thanks to the adjustable handle, it is possible to precisely adjust the direction of the light beam.

L- beam angle
31-165°x3°

C - colour



Catalogue code	Luminaire light flux	Power	Weight	Dimensions	Box dimensions
9185.05LC	200lm	4 x1W	0,7 kg	Ø 90mm, H=75mm	200x200x200mm

Accessories

embranchment IP67

catalogue code 90.10

