






GLARE CONTROL

LIGHTING CONTROL

FLICKER MANAGEMENT



## Compose Adjustable Lens

SKU	W	Lm @4000K	Tilt (T) Rotation (R) °	Cutout (mm)	Dimensions (mm)
G2-C1A10	10	1090	(T)20°	Ø 90-95	
G2-C2A13	13	1305	(T)20°	Ø 100-110	
G2-C3A10	10	1130	(T)20°	Ø 140-150	
G2-C3A18	18	1975	(T)20°	Ø 140-150	
G2-C3A25	25	2825	(T)20°	Ø 140-150	



RoHS



\* Only < 13W

### Physical

**Housing** PC/Aluminium

**Reflector Finish** Black, White, Silver, Matte Silver

**Trim Finish** White, Black

**Mounting Type** Recessed

### Electrical

**Voltage**


AC 220-240v 50/60Hz

**Control**

Non-dimmable, Triac, 1-10V, DALI

### Optical

**Beam Angle**



**CCT** 2700, 3000, 4000, 5000K

**CRI** 90, 97CRI

**SDCM** 3

**UGR** < 19

**Efficiency** >100lm/W @4000K

### Certification

**Warranty** 5 years

**Lifetime** L90 54,000Hrs

**Category**

AS/NZS 60598.2.2A

