

Thrive

Adjustable

SKU	W	Lm @4000K/@90CRI	Tilt (T) Rotation (R) °	Cutout (mm)	Dimensions (mm)
G2-T1A3	3W	380	25T x 355R	Ø 35	58
G2-T2A6	6W	400	25T x 355R	Ø 55	71
G2-T3A12	12W	950	25T x 355R	Ø 75	90
G2-T4A18	18W	1490	25T x 355R	Ø 105	139
*Trimless G2-T2TA6	6W	400	25T x 355R	Ø 55	71
*Trimless G2-T3TA12	12W	950	25T x 355R	Ø 75	90
*Trimless G2-T4TA18	18W	1490	25T x 355R	Ø 105	139

Physical

Housing Aluminium

Reflector Finish Black, White

Trim Finish White, Black

Mounting Type Recessed

Electrical

Voltage


AC 220-240v 50/60Hz

Control

Non-dimmable, Triac, DALI

Optical

Beam Angle



CCT 2700, 3000, 4000

CRI 90, 97, Thrive*

UGR < 19

Efficiency 63-83Lm/W

Lifetime L80< 50,000 Hrs

Certification

Warranty 5 years

Category

AS/NZS 60598.2.2A

TM21 report on request



CE RoHS **Bridgelux Thrive LED Technology** * Thrive LED specifications available on request

Accessories:

- Honeycomb: G2-TXA-H
- Softening lens: G2-TXA-SL
- Linear lens: G2-TXA-LL