



SKU	W	Lm @4000K/@90CRI	Tilt (T) Rotation (R) °	Cutout (mm)	Dimensions (mm)
G2-T1F3	3W	215	Fixed	Ø 25	Ø 32, 64
G2-T2F6	6W	470	Fixed	Ø 35	Ø 41, 93
G2-T3F9	9W	700	Fixed	Ø 45	Ø 52, 92
G2-T4F12	12W	960	Fixed	Ø 55	Ø 62, 107
*Trimless G2-T1TF3	3W	215	Fixed	Ø 35	50, 62
*Trimless G2-T2TF6	6W	470	Fixed	Ø 45	60, 93
*Trimless G2-T3TF9	9W	700	Fixed	Ø 55	80, 91
*Trimless G2-T4TF12	12W	960	Fixed	Ø 65	90, 108

Thrive Fixed

Physical

Housing Aluminium

Reflector Finish Black, White

Trim Finish White, Black, Silver

Mounting Type Recessed

Electrical

Voltage


AC 220-240v 50/60Hz

Control

Non-dimmable, Triac, DALI

Optical

Beam Angle *Beam angle options vary with size



CCT 2700, 3000, 4000

CRI 90, 97, Thrive*

UGR < 19

Efficiency 71-80Lm/W

Lifetime L80< 50,000 Hrs

Certification

Warranty 5 years

Category

AS/NZS 60598.2.2A

TM21 report on request



**Bridgelux Thrive
LED Technology**

* Thrive LED specifications available on request