



Thrive Nano

| SKU | W | Lm @4000K/@90CRI/50° | Tilt (T) Rotation (R) ° | Cutout (mm) | Dimensions (mm) |
|----------|-----|-------------------------|----------------------------|----------------|--------------------|
| G2-T1N6 | 6W | 400 | Fixed | Ø 55 | |
| G2-T2N9 | 9W | 650 | Fixed | Ø 65 | |
| G2-T3N12 | 12W | 950 | Fixed | Ø 75 | |
| G2-T4N18 | 18W | 1440 | Fixed | Ø 90 | |

CE RoHS



Bridgelux Thrive
LED Technology

* Thrive LED specifications
available on request

Physical

Housing Aluminium

Reflector Finish Matt Black,
Matt Silver, Matt White

Trim Finish White, Black

Mounting Type Recessed

Electrical

Voltage


AC 220-240v 50/60Hz

Control

Non-dimmable,
DALI

Optical

Beam Angle * Beam angles vary by size



CCT 2700, 3000, 4000, 5000K

CRI 90, 97 Thrive

UGR < 19

Efficiency 66-80lm/W

Lifetime L80 < 50,000 Hrs

Certification

Warranty 5 years

Category

AS/NZS 60598.2.2A

TM21 report on request



grace